
Maximum branch coefficient of relay protection



Overview

(of a relay) The extent of the protection afforded by a relay in terms of the impedance or circuit length as measured from the relay location.

Key Takeaways

The maximum branch coefficient in relay protection is typically determined by the percentage restraint or slope settings of differential relays, balancing sensitivity and security to prevent false tripping while ensuring internal faults are detected.

Definition and Role

In differential protection schemes, the branch coefficient (or slope factor) defines how much through current (restraint) is allowed before the relay operates. It is a key parameter in percentage-restrained differential relays, which measure the difference between incoming and outgoing currents in a protected zone. The operate-to-restraint ratio ensures that the relay trips for internal faults while remaining stable for external faults or CT saturation conditions.

Typical Values and Considerations

The slope characteristic of a relay determines the maximum branch coefficient. A higher slope increases restraint, improving security against false trips due to CT errors or load unbalance, but reduces sensitivity to low-level internal faults. For transformer differential protection, typical slope settings range from 20% to 50% for low-voltage windings and 30% to 60% for high-voltage windings, depending on CT accuracy, fault current levels, and system configuration.

© 2026 BAGYOU FIBRE NETWORKS · All rights reserved

The maximum branch coefficient is constrained by the need to maintain selectivity and sensitivity. Excessive restraint may prevent the relay from tripping during genuine internal faults, while too low a coefficient may cause nuisance tripping during through currents or inrush conditions.

Practical Application

Engineers must consider CT saturation, inrush currents, and load conditions when setting the branch coefficient.

The IE

C standards and relay manufacturer guidelines provide recommended ranges for slope and restraint settings to ensure proper coordination with upstream and downstream relays. In multi-branch systems, the coefficient may be adjusted for each branch to account for differences in line impedance, fault contribution, and relay location, ensuring selective tripping and minimizing supply interruptions.

Summary

The maximum branch coefficient is not a fixed universal value but is determined by the relay type, system configuration, and protection objectives. It is set to maximize security against false trips while maintaining sensitivity to internal faults, typically within the 20–60% range for most transformer and bus differential applications. Proper calculation and testing are essential to ensure reliable and selective protection.

Article Content

Circuit Protection Methods

Combining with faults occurring at different locations along the feeder line, the composition and basic working principle of the FCL are discussed, the theory of fast fault identification method

Part 9 – Sizing Motor Overload Protection and OCPDs

NEC Article 430, Part III provides guidelines for sizing overload protection devices such as, overload relays, fuses and circuit breakers for motor branch circuit conductors against excessive heating

Percentage Restrained Differential, Percentage of What?

Equation (6) applies to relays using MAXIMUM restraint. Equation (5) is derived by assuming that the error is subtractive and reduces e ther the current entering the zone

Power System Protective Relays: Principles & Practices

© 2026 BAGYOU FIBRE NETWORKS - All rights reserved

(of a relay) The extent of the protection afforded by a relay in terms of the impedance or circuit length as measured from the relay location. Note: The measurement is usually to a point of fault, but excessive

Efficient searching of extreme operating conditions for relay ...

In this regard, correctly identifying EOCs is essential for calculating the settings of backup relay protection. Therefore, the research problem of this paper is to accurately identify the extreme

Protective Relaying Philosophy and Design Guidelines

For relays with multiple reactance zones, the distance relay transient load limit (DRTLL) should be computed for all zones up to and including the zone where the maximum bulge point is located.

FEEDER PROTECTION CALCULATIONS & SETTINGS

Relay 8 backs up relays 6 and 7, and should be co-ordinated with the slowest of these two relays. Relay 7 has an instantaneous setting of 1100 A, which is smaller than the setting of relay 6, and so the

Application Guidelines for Ground Fault Protection

Originally presented at the 24th Annual Western Protective Relay Conference, October 1997

Fundamentals of Modern Protective Relaying

A primary motor protective element of the motor protection relay is the thermal overload element and this is accomplished through motor thermal image modeling. This model must account for thermal

SPDTableOfContents.qxd

Ground fault protection is equipment protection from the effects of ground faults. The National Electrical Code® (NEC®) has specific ground fault equipment protection requirements in 215.10, 230.95,

Distribution Automation Handbook

Time-graded protection is implemented using overcurrent relays with either definite time characteristic or inverse time characteristic. The operating time of definite time relays does not depend on the

Operation Control Method of Relay Protection in Flexible DC ...

The adaptive weight and WOA are employed to obtain the optimal strategy for relay protection operation control, reducing the action time and impulse current. Experimental results demonstrate the

© 2026 BAGYOU FIBRE NETWORKS - All rights reserved

Setting Calculation Method and Protection Coordination for Relay ...

Then, the electrical engineering software is used to perform a more accurate setting calculation and protection coordination. Also, the arc flash hazard is weakened by the arc flash protection device.

Introduction to Protective Relaying | Electric Power Measurement and ...

Introduction to Protective Relaying What are Protective Relays, or Protection Relays? Protective relays are used in industrial power generation and supply systems to open and isolate branch circuits in the

CHAPTER-3

Multi function protective relays may be cost effective for generator and line protection when many individual relays are required. When multifunctional relays are selected limited back up conventional

Circuit Protection Methods

Circuit protection includes protection from equipment overload conditions, undervoltage and overvoltage conditions, ground faults, and short circuits. Although mandated by code for any electrical

Relay Protection in HV/MV Substations: Calculations, Settings ...

Introduction Relay protection is essential to ensure the stability, reliability, and safety of electrical power systems. In HV (High Voltage) and MV (Medium Voltage) substations, relay

The fundamentals of protection relay co-ordination and time ...

Among the various possible methods used to achieve correct relay co-ordination are those using either time or overcurrent, or a combination of both.

© 2026 BAGYOU FIBRE NETWORKS - All rights reserved

Contact Us

Continue your research online:

Website: https://bagyou.es
Technical inquiry: https://bagyou.es/project-enquiry.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 BAGYOU FIBRE NETWORKS - All rights reserved